


### 3391 Sella 2 - STWB

Housing and cover: in die-cast aluminium and designed with a very small surface exposed to wind. Cooling fins are integrated into the cover. Optics: in aluminium coated with very high purity (99.99%) silver using physical vapour deposition (PVD). Pole connection: in die-cast aluminium and with gaskets to secure the frame according to different inclinations. Adjustable ranges: between 0° and 20° for side mount; and between 0° and 20° for mast-top mounting. Inclination pace: 5°. Suited for poles with a diameter 42-76. Diffuser: extra-clear, tempered glass, 4 mm thick, resistant to thermal shock and impacts (UNI-EN12150-1: 2001). Coating: the standard powder coating consists of a first metal surface pre-treatment stage and of single layer of UV-stabilised, corrosion and salt resistant polyester powder coating. The SELLA luminaire is declared to have passed the 2000 hours of salt corrosion resistance test in accordance with ASTM B 117 standard and the 2000 hours of UV condensation test in accordance with the ASTM G 154 standard. Standard supply: double insulation switch that cuts off electricity when the cover is opened. Electronic safety device to protect the LED module and the related ballast compliant with EN 61547. External connector for quick installation. It works in two modes: - differential mode: surge between power cables and between the phase and neutral. - common mode: surge between power, L/N and ground cables or between the fixture's body if it is of class II and installed on a metal pole. Upon request: protection up to 10KV. Coating compliant with UNI EN ISO 9227 Corrosion tests in artificial atmospheres for aggressive environments. Wind surface: 2640cm².

LED: Luminous flux maintenance (including end-of-life failure) Sella 2 L80B10  
 @ta+25°C L80B10  
 @ta+50°C L90B10  
 @ta+25°C L90B10  
 @ta+50°C n.LED W 32 170 (700mA) >100.000h >100.000h 70.000h 50.000h 40 208 (700mA) >100.000h >100.000h 70.000h 50.000h 48 255 (700mA) >100.000h >100.000h 60.000h 40.000h  
 Registered Design DM/100271



#### Download

DXF 2D  
 - 3390-3391.dxf

#### 3DS

- disano\_3391\_sella2\_40\_led.3ds  
 - disano\_3391\_sella2\_48\_led.3ds  
 - disano\_3391\_sella2\_32\_led.3ds

#### 3DM

- disano\_3391\_sella2\_48\_led.3dm  
 - disano\_3391\_sella2\_40\_led.3dm  
 - disano\_3391\_sella2\_32\_led.3dm

#### Montaggi

- sella1-2.pdf

Code	Gear	Kg	Lumen-K-CRI	WTot	Colour	Surge
330813-00	CLD CELL	11,20	LED-20495lm-700mA-4000K-CRI 70	170 W	GREY	6/8kV
330810-00	CLD CELL	11,16	LED-20495lm-700mA-4000K-CRI 70	170 W	GRAFITE	6/8kV
330814-00	CLD CELL	11,60	LED-25618lm-700mA-4000K-CRI 70	208 W	GREY	4/6kV
330811-00	CLD CELL	11,40	LED-25618lm-700mA-4000K-CRI 70	208 W	GRAFITE	4/6kV
330815-00	CLD CELL	11,64	LED-30742lm-700mA-4000K-CRI 70	255 W	GREY	6/8kV
330812-00	CLD CELL	11,71	LED-30742lm-700mA-4000K-CRI 70	255 W	GRAFITE	6/8kV
330813-39	CLD CELL	11,26	LED-19060lm-700mA-3000K-CRI 70	170 W	GREY	6/8kV
330810-39	CLD CELL	11,14	LED-19060lm-700mA-3000K-CRI 70	170 W	GRAFITE	6/8kV
330814-39	CLD CELL	11,60	LED-23825lm-700mA-3000K-CRI 70	208 W	GREY	4/6kV
330811-39	CLD CELL	11,40	LED-23825lm-700mA-3000K-CRI 70	208 W	GRAFITE	4/6kV
330815-39	CLD CELL	11,64	LED-28590lm-700mA-3000K-CRI 70	255 W	GREY	6/8kV
330812-39	CLD CELL	11,71	LED-28590lm-700mA-3000K-CRI 70	255 W	GRAFITE	6/8kV

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated