



Product Datasheet

15 Plafo>The LED Plafo Range

67390/W/W



21W LED slim plafo, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.












Downloads







Dimensions




Physical Specification

Product Type	Gear
Item Group	15 Plafo
Family	The LED Plafo Range
Order Code	67390/W/W
Colour	White
Material	ABS
Diffuser Material	PC
Diffuser Color	Opal
Shape	Circular
Height	63mm
Diameter	320mm
Surface Ceiling	Yes

Indoor	Yes
Outdoor	Yes
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
	000.040\/
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	21W
IP Rating	IP65
Light Source	LED built in
Dimmable	No VEZ
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	40V
Power(Watts)	20W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	120
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	13,5-21W
Power Factor	0,9
Constant Current	Yes
500mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Manufacturer	Eaglerise
Ilumination Data	
Colour Temperature	3000K
Colour Temperature Lumen Output	3000K 1300lm
Lumen Output	1300lm
Lumen Output Light Efficiency	1300lm 61,9lm/W
Lumen Output Light Efficiency CRI	1300lm 61,9lm/W
Lumen Output Light Efficiency CRI Illumination Diagram	1300lm 61,9lm/W
Lumen Output Light Efficiency CRI	1300lm 61,9lm/W
Lumen Output Light Efficiency CRI Illumination Diagram	1300lm 61,9lm/W
Lumen Output Light Efficiency CRI Illumination Diagram	1300lm 61,9lm/W 80
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length	1300lm 61,9lm/W 80 33cm
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width	1300lm 61,9lm/W 80 33cm
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height	1300lm 61,9lm/W 80 33cm 33cm 7,5cm
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	1300lm 61,9lm/VV 80 33cm 7,5cm 1,49Kg
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight Pcs/Carton	1300lm 61,9lm/W 80 33cm 33cm 7,5cm 1,49Kg



Certification & Warranty

Warranty	2 Years
Wee Directive	Yes

switch to one light!

